

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

223 REMINGTON

55,000 PSI -- STANDARD SAAMI COMMERCIAL SPECIFICATIONS

Barrel: 24" | Twist: 1-12" | Primer: WIN WSR | Bullet Diameter: 0.224"
Case: WIN | Max Case Length: 1.760" | Trim Length: 1.750"

ACCURATE 5744

35	HDY	V-MAX	19.2	3,169	21.1	3,602	53,694	2.130
40	NOSLER	B-TIP	18.5	3,025	20.6	3,439	54,810	2.260
50	BARNES	VARM	17.8	2,743	19.7	3,117	52,983	2.235
53	HDY	HP	16.8	2,626	18.7	2,985	53,897	2.225
55	SIERRA	SPT	16.8	2,612	18.7	2,968	54,990	2.230

223 REMINGTON *(continued)*

55,000 PSI -- STANDARD SAAMI COMMERCIAL SPECIFICATIONS

ACCURATE LT-30

36	BARNES	VG	21.1	3,425	23.5	3,735	54,813	2.200
40	BERGER	FBV	21.0	3,356	23.4	3,676	54,936	2.200
40	HDY	V-MAX	21.5	3,377	23.9	3,699	54,627	2.200
40	NOSLER	BTLF	20.8	3,276	23.2	3,602	54,625	2.260
42	SF	WTP	21.0	3,296	23.3	3,604	54,928	2.200
50	HDY	GMX	19.2	2,882	21.4	3,153	54,971	2.165
50	SIERRA	BK	20.3	3,053	22.6	3,332	54,907	2.260
52	NOSLER	HPBT-CC	20.0	3,009	22.2	3,257	54,381	2.237
53	BARNES	TSX-FB	19.6	2,922	21.7	3,186	54,888	2.200
55	HDY	V-MAX	19.4	2,860	21.5	3,114	54,833	2.260
55	HDY	GMX	17.4	2,645	19.3	2,879	54,699	2.185
55	NOSLER	VARMGT	19.6	2,907	21.7	3,147	54,789	2.260
62	BARNES	TSX-BT	17.8	2,659	19.8	2,895	54,690	2.260
64	BERGER	FBV	18.0	2,681	19.4	2,809	54,936	2.260
68	HDY	BTHP	17.8	2,585	19.8	2,815	54,969	2.250
77	SIERRA	HPBT	16.5	2,342	18.3	2,539	54,836	2.260

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

ACCURATE 2200

30	BARNES	VG	24.9	3,833	27.7	4,189	54,780	2.100
34	MSS	VNX	24.3	3,682	27.0	4,024	53,730	2.125
35	NOSLER	BTLF	23.2	3,635	25.8	3,936	54,689	2.260
36	BARNES	VG	23.8	3,518	26.4	3,863	54,789	2.190
40	BERGER	FBV	22.6	3,386	25.1	3,700	54,650	2.224
40	HDY	V-MAX	23.1	3,419	25.7	3,737	53,955	2.260
40	NOSLER	B-TIP	22.9	3,386	25.4	3,701	53,740	2.260
40	NOSLER	BTLF	22.2	3,384	24.7	3,679	54,910	2.260
40	SIERRA	BK	22.9	3,400	25.4	3,716	54,356	2.260
42	SF	WTP	22.4	3,395	24.9	3,676	54,669	2.200
45	SIERRA	SPT	22.0	3,219	24.4	3,518	54,253	2.230
45	BARNES	BAND-S	23.3	3,343	25.9	3,654	54,621	2.220
45	BARNES	TSX-FB	22.6	3,247	25.1	3,549	54,550	2.220
50	BERGER	FBV	21.0	3,025	23.3	3,306	54,023	2.260
50	HDY	SP	21.5	3,063	23.9	3,348	54,621	2.235
50	SIERRA	BK	22.1	3,111	24.6	3,400	53,998	2.260
50	MSS	VNX	20.7	3,056	23.0	3,340	53,260	2.187
50	BARNES	TSX-FB	21.2	3,013	23.6	3,293	54,734	2.195
52	NOSLER	HPBT-CC	21.4	3,011	23.8	3,291	53,429	2.236
53	BARNES	TSX-FB	20.7	2,936	23.0	3,209	54,316	2.213
55	BERGER	FBV	21.0	2,898	23.3	3,167	54,243	2.260
55	HDY	BT-FMJ	20.4	2,936	22.7	3,202	54,395	2.200
55	HDY	SP	20.5	2,846	22.8	3,110	53,233	2.220
55	NOSLER	B-TIP	21.1	2,904	23.4	3,174	52,974	2.260
55	SIERRA	HPBT GK	20.6	2,890	22.9	3,159	54,159	2.175
55	SIERRA	SBT	20.9	2,934	23.2	3,207	54,317	2.230
55	MSS	VNX	19.8	2,890	22.0	3,175	54,300	2.162
55	BARNES	TSX-FB	20.0	2,798	22.2	3,058	53,713	2.190
55	BARNES	MPG	19.0	2,745	21.1	2,977	54,000	2.180
55	SF	NTP	19.7	2,859	21.9	3,157	54,632	2.260
60	NOSLER	PART	19.3	2,713	21.4	2,965	54,513	2.220

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)	
<u>ACCURATE 2015</u>									
30	BARNES	VG	22.9	3,450	25.4	3,771	49,940	2.088	C
34	MSS	VNX	23.9	3,489	26.5	3,813	54,040	2.125	C
40	BERGER	FBV	22.5	3,220	25.0	3,519	53,060	2.210	C
40	HDY	V-MAX	22.9	3,288	25.4	3,593	54,890	2.260	C
40	NOSLER	B-TIP	22.7	3,256	25.2	3,558	54,961	2.260	C
40	SIERRA	BK	22.7	3,261	25.2	3,564	54,440	2.260	C
45	SIERRA	SPT	21.8	3,088	24.2	3,375	54,980	2.222	
50	BERGER	FBV	21.0	2,933	23.3	3,206	54,110	2.260	
50	HDY	SPSX	21.2	2,943	23.6	3,216	54,900	2.180	
50	HDY	V-MAX	21.6	2,984	24.0	3,261	54,990	2.260	C
50	HDY	SP	21.3	2,937	23.7	3,210	54,000	2.226	
50	SIERRA	BK	21.6	2,964	24.0	3,239	53,750	2.260	C
50	MSS	VNX	21.4	2,965	23.8	3,240	53,550	2.187	
50	BARNES	TSX-FB	20.8	2,855	23.1	3,120	53,830	2.184	
52	BERGER	FBV	21.2	2,895	23.5	3,180	54,750	2.260	
52	NOSLER	HPBT-CC	21.2	2,906	23.6	3,176	54,080	2.226	
53	BARNES	TSX-FB	20.4	2,750	22.7	3,050	54,950	2.202	
55	BERGER	FBV	20.9	2,795	23.2	3,075	54,750	2.244	
55	HDY	BT-FMJ	20.9	2,804	23.2	3,105	54,813	2.200	
55	HDY	SPSX	20.3	2,750	22.5	3,005	53,010	2.195	
55	HDY	V-MAX	20.3	2,735	22.5	3,025	54,800	2.260	
55	NOSLER	B-TIP	20.9	2,804	23.2	3,065	53,960	2.260	
55	SIERRA	HPBT GK	21.0	2,804	23.3	3,064	54,060	2.160	
55	MSS	VNX	20.6	2,800	22.9	3,095	54,900	2.162	
55	BARNES	TSX-FB	19.8	2,685	22.0	2,966	54,850	2.183	
60	NOSLER	PART	19.4	2,628	21.5	2,872	54,050	2.205	
60	SIERRA	HP	20.3	2,691	22.6	2,941	54,990	2.232	
62	MIL	M855	20.4	2,660	22.7	2,916	54,517	2.260	
62	BARNES	TSX-BT	20.5	2,669	22.8	2,935	54,882	2.255	C
65	SIERRA	SBT	19.6	2,562	21.8	2,806	53,813	2.210	
68	HDY	BTHP-M	19.5	2,506	21.7	2,777	54,239	2.250	
69	SIERRA	HPBT	19.7	2,524	21.8	2,762	54,930	2.245	
70	BARNES	TSX-FB	19.0	2,441	21.1	2,690	53,972	2.260	
75	HDY	BTHP-M	19.1	2,425	21.2	2,652	54,918	2.260	
77	SIERRA	HPBT MK	18.5	2,333	20.5	2,553	54,702	2.260	
80	SIERRA	HPBT MK	19.5	2,349	21.7	2,582	54,655	2.260	C
90	SIERRA	HPBT MK	19.0	2,198	21.1	2,400	54,520	2.260	C

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)	
<u>RAMSHOT X-TERMINATOR</u>									
30	BARNES	VG	26.1	3,687	29.0	4,029	51,560	2.088	C
34	MSS	VNX	26.6	3,665	29.5	4,006	53,570	2.125	C
35	NOSLER	BTLF	25.8	3,626	28.7	3,947	54,709	2.260	C
36	BARNES	VG	25.6	3,510	28.5	3,820	53,086	2.190	C
40	BERGER	FBV	23.9	3,451	26.5	3,772	54,360	2.210	
40	HDY	V-MAX	24.3	3,480	27.0	3,803	54,750	2.260	
40	NOSLER	B-TIP	24.3	3,435	27.0	3,754	53,760	2.260	
40	SIERRA	BK	24.3	3,459	27.0	3,780	54,640	2.260	
40	NOSLER	BTLF	24.5	3,435	27.2	3,721	54,448	2.260	C
42	SF	WTP	25.3	3,437	28.1	3,730	54,490	2.200	C
45	SIERRA	SPT	23.2	3,296	25.8	3,602	54,960	2.222	
45	BARNES	BAND-S	24.3	3,309	27.0	3,616	54,650	2.216	
45	BARNES	TSX-FB	24.1	3,276	26.8	3,580	54,560	2.208	
45	SF	WTP	24.3	3,186	27.0	3,540	54,177	2.224	C
50	BERGER	FBV	22.1	3,122	24.6	3,412	54,890	2.260	
50	HDY	SPSX	22.1	3,093	24.5	3,380	54,740	2.180	
50	HDY	V-MAX	22.2	3,115	24.7	3,404	53,460	2.260	

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

55,000 PSI -- STANDARD SAAMI COMMERCIAL SPECIFICATIONS

RAMSHOT X-TERMINATOR *(continued)*

50	HDY	SP	22.4	3,128	24.9	3,419	54,760	2.226
50	NOSLER	B-TIP	23.4	3,134	26.2	3,413	54,692	2.260
50	MSS	VNX	22.5	3,114	25.0	3,403	54,490	2.187
50	SIERRA	BK	22.9	3,143	25.4	3,435	54,160	2.260
50	BARNES	VG	23.0	3,007	25.5	3,341	54,211	2.180
50	BARNES	TSX-FB	22.7	3,082	25.2	3,368	54,770	2.184
52	BERGER	FBV	22.1	3,088	24.6	3,375	54,950	2.260
52	NOSLER	HPBT-CC	22.1	3,059	24.6	3,343	53,360	2.226
53	BARNES	TSX-FB	22.3	3,015	24.8	3,295	54,700	2.202
55	BERGER	FBV	21.3	2,965	23.7	3,240	54,960	2.244
55	HDY	BT-FMJ	22.4	2,976	24.9	3,278	54,466	2.200
55	HDY	SPSX	21.4	2,949	23.8	3,223	54,100	2.195
55	HDY	V-MAX	21.2	2,936	23.5	3,209	54,210	2.260
55	NOSLER	B-TIP	22.1	2,983	24.5	3,260	54,640	2.260
55	SIERRA	SBT	22.2	3,028	24.7	3,309	54,980	2.215
55	SIERRA	HPBT GK	22.2	3,007	24.7	3,286	54,760	2.160
55	MSS	VNX	21.6	2,943	24.0	3,216	53,220	2.162
55	BARNES	TSX-FB	21.8	2,914	24.2	3,185	54,950	2.183
55	BARNES	MPG	23.3	2,946	25.9	3,186	54,900	2.180
55	SF	NTP	22.5	2,997	25.0	3,285	54,987	2.260
60	HDY	V-MAX	21.0	2,795	23.3	3,082	54,976	2.250
60	NOSLER	PART	21.2	2,836	23.6	3,099	54,350	2.205
60	SIERRA	HP	20.9	2,815	23.2	3,077	54,060	2.232
62	MIL	M855	21.4	2,778	23.8	3,050	54,137	2.260
62	BARNES	TSX-BT	22.1	2,833	24.5	3,100	54,001	2.255
65	SIERRA	SBT	21.0	2,738	23.4	2,982	54,399	2.210
68	HDY	BTHP-M	21.3	2,721	23.7	2,977	54,650	2.250
69	SIERRA	HPBT	20.7	2,666	23.1	2,895	54,430	2.245
70	BARNES	TSX-BT	21.0	2,670	23.3	2,904	54,636	2.260
75	HDY	BTHP-M	20.4	2,563	22.7	2,794	54,279	2.260

C

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
77	SIERRA	HPBT MK	20.2	2,531	22.2	2,731	54,300	2.260
80	SIERRA	HPBT MK	20.8	2,528	23.1	2,732	54,440	2.260
90	SIERRA	HPBT MK	19.6	2,393	21.8	2,542	54,675	2.260

ACCURATE 2230

30	BARNES	VG	26.1	3,687	29.0	4,029	51,560	2.088	C
34	MSS	VNX	26.6	3,665	29.5	4,006	53,570	2.125	C
35	NOSLER	BTLF	25.8	3,626	28.7	3,947	54,709	2.260	C
36	BARNES	VG	25.6	3,510	28.5	3,820	53,086	2.190	C
40	BERGER	FBV	23.9	3,451	26.5	3,772	54,360	2.210	
40	NOSLER	BTLF	24.5	3,435	27.2	3,721	54,448	2.260	
40	HDY	V-MAX	24.3	3,480	27.0	3,803	54,750	2.260	
40	NOSLER	B-TIP	24.3	3,435	27.0	3,754	53,760	2.260	
40	SIERRA	BK	24.3	3,459	27.0	3,780	54,640	2.260	C
42	SF	WTP	25.3	3,437	28.1	3,730	54,490	2.200	C
45	SIERRA	SPT-V	23.2	3,296	25.8	3,602	54,990	2.222	
45	BARNES	BAND-S	24.3	3,309	27.0	3,616	54,650	2.216	
45	BARNES	TSX-FB	24.1	3,276	26.8	3,580	54,560	2.208	
45	SF	WTP	24.3	3,186	27.0	3,540	54,177	2.224	C
50	BERGER	FBV	22.1	3,122	24.6	3,412	54,890	2.260	
50	HDY	SPSX	22.1	3,093	24.5	3,380	54,740	2.180	
50	HDY	V-MAX	22.2	3,115	24.7	3,404	53,460	2.260	
50	HDY	SP	22.4	3,128	24.9	3,419	54,760	2.226	
50	NOSLER	B-TIP	23.5	3,134	26.2	3,413	54,692	2.260	
50	MSS	VNX	22.5	3,114	25.0	3,403	54,490	2.187	
50	SIERRA	BK	22.9	3,143	25.4	3,435	54,160	2.260	
50	BARNES	VG	23.0	3,007	25.5	3,341	54,211	2.180	
50	BARNES	TSX-FB	22.7	3,082	25.2	3,368	54,770	2.184	
52	BERGER	FBV	22.1	3,088	24.6	3,375	54,990	2.260	
52	NOSLER	HPBT-CC	22.1	3,059	24.6	3,343	53,360	2.226	
53	BARNES	TSX-FB	22.3	3,015	24.8	3,295	54,700	2.202	
55	BERGER	FBV	21.3	2,965	23.7	3,240	54,960	2.244	
55	HDY	BT-FMJ	22.4	2,976	24.9	3,278	54,466	2.200	
55	HDY	SPSX	21.4	2,949	23.8	3,223	54,100	2.195	